

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4307C

Revision 6

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel				
1.	Identification code of the produ		1.4307 – EN 10088-4:2009	
2.	Туре		1.4307 See marking / label / inspection certificate	
3.			Building Construction or Civil Engineering	
			Columbus Stainless (Pty) Ltd	
4.	Manufacturer		Hendrina Road, Middelburg, South Africa,	
			1050	
5.	. Authorised Representative in the EU		Acerinox Europa S.A.U. C/ Santiago de	
0.	•		Compostela nº 100. 28035 Madrid, Spain	
6.	Assessment system and verific		EN 10088-4, Annex ZA, System 2+	
	constancy of performance as per Annex V			
	The Notified Body: has conducted the first inspection and		TÜV Rheinland Polska Sp. z o.o. 2+	
7.	continuous surveillance according to the			
	system:			
	and issued the certificate:			R-B.ZA0001.TÜVRh.22.00
	as a confirmation of conformity	for the factory		
	production control			
8.	Construction product with European Technical Assessment: No			
9. Declared Performance:				
	Essential Characteristics	Performa	ince	Harmonised Technical Specification
	Tolerances on Dimensions	Tables 1, 2, 3	& 4	
	Tolerances on Dimensions and Shape		& 4	Harmonised Technical Specification ISO 9445-2:2009
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1, 2, 3	& 4	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 Paragraphs 11	& 4	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3 Paragraphs 11 520-700MPa	& 4	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa	& 4	ISO 9445-2:2009
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45%	& 4	ISO 9445-2:2009
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45%	& 4	ISO 9445-2:2009
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation • Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 Paragraphs 11 520-700MPa ≥220MPa ≥45% N/A Table 3 Table 3 Table 10	& 4 , 12 & 13	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009

10. The performance of the product is in accordance with the specification given above.

This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

DJ Kruger: Business Unit Manager Technical Signed at Middelburg, South Africa on the 17th day of March 2023