

DECLARATION OF PERFORMANCE

(according to Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended

Document no.:

TEC-DOP-UKC4432C

Revision 0

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	1			1.4432 – EN 10088-4:2009	
2.	Туре		1.4432 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Hendrina I		us Stainless (Pty) Ltd	
4.	Manufacturer			na Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the UK		Acerinox U.K. Ltd., Heath Road, Darlaston West Midlands WS10 8XL		
6.	Assessment system and verific		TUV Rheinland UK Ltd.		
U.	constancy of performance as p	er Annex V			
	The Notified Body:	_			
	has conducted the first inspection and				
7.	continuous surveillance according to the		2+ 2571-UK-CPR-A304		
	system: and issued the certificate:				
	as a confirmation of conformity	for the factory	257 I-UK	-CPR-A304	
	production control	Tor the factory			
8.	Construction product with European Technical Assessment: No				
	Declared Performance:				
<u> </u>					
	Econtial Characteristics	Dorforma		Harmaniand Tachnical Specification	
	Essential Characteristics	Performa		Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1, 2, 3	& 4	Harmonised Technical Specification	
	Tolerances on Dimensions and Shape		& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1, 2, 3	& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 o Paragraphs 11	& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3 of Paragraphs 11	& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3 Table 10	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 of Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

DJ Kruger: Business Unit Manager Technical

Signed at Middelburg, South Africa on the 6th day of March 2024